

PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference P04690PC/ALi	FOR FURTHER ACTION See Notification of Transmittal of International Preliminary Examination Report (Form PCT/IPEA/416)	
International application No. PCT/SE00/00083	International filing date (day/month/year) 17.01.2000	Priority date (day/month/year) 15.01.1999
International Patent Classification (IPC) or national classification and IPC ₇ B 01 F 3/04, B 01 F 7/00		
Applicant Gefle Virvelteknik AB et al		

1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.

2. This REPORT consists of a total of 3 sheets, including this cover sheet.

☒ This report is also accompanied by ANNEXES, i.e., sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).

These annexes consist of a total of 5 sheets.

3. This report contains indications relating to the following items:

- I ☒ Basis of the report
- II ☐ Priority
- III ☐ Non-establishment of opinion with regard to novelty, inventive step and industrial applicability
- IV ☐ Lack of unity of invention
- V ☒ Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement
- VI ☐ Certain documents cited
- VII ☐ Certain defects in the international application
- VIII ☐ Certain observations on the international application

Date of submission of the demand 28.07.2000	Date of completion of this report 20.04.2001
Name and mailing address of the IPEA/SE Patent- och registreringsverket Box 5055 S-102 42 STOCKHOLM Facsimile No. 08-667 72 88	Authorized officer Wiva Asplund/ELY Telephone No. 08-782 25 00

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/SE00/00083

I. Basis of the report

1. With regard to the **elements** of the international application:*

- ☐ the international application as originally filed
- ☒ the description:
pages 1-5, 7-13, as originally filed
pages _____, filed with the demand
pages 6, filed with the letter of 15.01.2001
- ☒ the claims:
pages _____, as originally filed
pages _____, as amended (together with any statement) under article 19
pages _____, filed with the demand
pages 14-16, filed with the letter of 15.01.2001
- ☒ the drawings:
pages 1-3, 5, as originally filed
pages _____, filed with the demand
pages 4, filed with the letter of 18.04.2001
- ☐ the sequence listing part of the description:
pages _____, as originally filed
pages _____, filed with the demand
pages _____, filed with the letter of _____

2. With regard to the **language**, all the elements marked above were available or furnished to this Authority in the language in which the international application was filed, unless otherwise indicated under this item.
These elements were available or furnished to this Authority in the following language _____ which is:

- ☐ the language of a translation furnished for the purposes of international search (under Rule 23.1(b)).
- ☐ the language of publication of the international application (under Rule 48.3(b)).
- ☐ the language of the translation furnished for the purposes of international preliminary examination (under Rules 55.2 and/or 55.3).

3. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international preliminary examination was carried out on the basis of the sequence listing:

- ☐ contained in the international application in written form.
- ☐ filed together with the international application in computer readable form.
- ☐ furnished subsequently to this Authority in written form.
- ☐ furnished subsequently to this Authority in computer readable form.
- ☐ The statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.
- ☐ The statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished.

4. ☐ The amendments have resulted in the cancellation of:

- ☐ the description, pages _____
- ☐ the claims, Nos. _____
- ☐ the drawings, sheet/fig _____

5. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2 (c)).**

* Replacement sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are annexed to this report since they do not contain amendments (Rules 70.16 and 70.17).

** Any replacement sheet containing such amendments must be referred to under item I and annexed to this report.

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

International application No.

PCT/SE00/00083

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**1. Statement**

Novelty (N)	Claims	<u>1-16</u>	YES
	Claims		NO
Inventive step (IS)	Claims	<u>1-16</u>	YES
	Claims		NO
Industrial applicability (IA)	Claims	<u>1-16</u>	YES
	Claims		NO

2. Citations and explanations (Rule 70.7)

The claimed invention relates to an apparatus and a method for treatment of contaminated media and a product obtained by the method. The apparatus includes a rotatable housing with at least one inlet for gas and one suction opening for the medium to be treated. A number of outlet openings with vanes are arranged along the periphery of the housing and a shaft is connected to the housing for causing rotation. The housing comprises at least one compartment shaped as a truncated cone with inlet for the medium to be treated at the apex of the cone and the outlets at the base of the cone.

Cited CA 1101138 A discloses an apparatus for mixing gases with a liquid. The apparatus includes a hollow rotatable shaft with an intake for gas near the top end and an outlet for gas near the bottom end and an impeller connected to the shaft. The impeller comprises two spaced-apart discs with a plurality of vanes therebetween and an aperture for intake of liquid adjacent the shaft. The impeller draws liquid through the aperture past the gas outlet and expels the liquid outwardly from the vanes as the impeller rotates.

The cited document does not disclose an apparatus for gas treatment of contaminated media including a rotatable housing shaped as a truncated cone with inlet for the medium to be treated at the apex of the cone and outlets at the base of the cone. This shape of the apparatus effects a very efficient oxygenation of the contaminated medium and a cavitation is created in the medium, which achieves a temperature increase, which contributes to a very high killing of bacteria.

Therefore, the claimed invention is novel, is considered to involve an inventive step and to be industrially applicable.

WO 00/41802

PCT/SE00/00083

6

from escaping upwards and into the atmosphere. In fact, the strong vortex in the vessel and the downward movement of the expelled medium combine to make the expelled medium quickly reentering the lower compartment through the bottom inlet 10. In order to further enhance the effect of this flow improvement, preferably
5 a vessel is used where the lower portion is cone shaped.

In Fig. 4 there is shown a simpler variant wherein the upper compartment has been removed. In all other respects it is identical with the embodiment shown in Fig. 3.

10

In the same way there is shown in Fig. 5, a variant wherein the lower compartment has been removed. For this purpose the shaft 24 is attached e.g. by means of welding in the plate 20, which forms a bottom. Radial holes 25 are bored through to the central air channel 26. In all other respects it is identical to the upper part of
15 the embodiment shown in Fig. 3. This variant can only be used for oxygenation.

Depending on the field of use the stirrer according to the invention can be differently dimensioned. It can be used in relatively small containers of a few hundred litres, up to very large containers of tens of cubic metres and even larger.

20

Another conceivable field of use is purification/oxygenation of water in lakes, whereby the stirrer could be made very large with a diameter of up to 1 m. Also water in fish breeding facilities could be treated in accordance with the invention.

25 Other conceivable fields of use are treatment of various types of manure such as manure from pigs and cows. Such manure types often contains straw and therefore need to be pre-treated by some kind of grinding process.

It is further conceivable to treat butchery wastes, leakage water from waste dumps,
30 process waters from industries, waste water from car wash facilities etc.

Still another use of the inventive idea is the removal of metals from waste waters, especially for the enhancement of the sedimentation rate of leachates from waste deposits. It is especially efficient for the improved separation of copper. For this
35 purpose a device according to Fig. 4 is used. It is believed that due to the extreme conditions created inside the stirrer housing, the Cu-microparticles will aggregate to larger assemblies that will sediment at a very much larger rate. It is also possible

WO 00/41802

PCT/SE00/00083

14

CLAIMS:

1. An apparatus for the treatment of contaminated media, comprising a rotatable housing having at least one inlet (28) for gas and at least one suction opening (10; 32) for the medium to be treated; a number of outlet openings (25; 27) arranged along the periphery of the housing; a number of vanes (22; 23) arranged in said outlet openings (35; 27); and a shaft (24) connected to the housing and connectable to a device for causing rotation of the housing;

10 c h a r a c t e r i z e d i n t h a t

the housing comprises at least one compartment which is essentially shaped as a truncated cone, with the inlet (10; 32) for the medium to be treated at the apex of the cone and the outlets (25; 27) at the base thereof.

15

2. The apparatus according to claim 1, wherein

said housing comprises an upper compartment (5) with a corresponding upper suction opening (32) and a lower compartment (7) with a corresponding lower suction opening (10), where the upper and the lower compartments are separated by a plate (20); and wherein

20

the plurality of outlet opening (25; 27) provided along the periphery of the housing or housings belong to the upper (5) and the lower (7) compartments respectively, at the opposite end thereof with respect to the corresponding suction opening (32, 10).

25

3. The apparatus according to claim 1, wherein said housing comprises one single compartment (7) having the shape of a truncated cone with the apex facing downwards, and having a suction opening (10) at the apex of said cone, and a plate (20) forming the base of said cone and closing said compartment (7), and wherein the gas inlet (28) exits through said plate (20).

30

4. The apparatus according to claim 1, wherein said housing comprises one single compartment (7) having the shape of a truncated cone with the apex facing

35

WO 00/41802

PCT/SE00/00083

15

upwards, and having a suction opening (32) at the apex of said cone, and a plate (20) forming the base of said cone and closing said compartment (7), and wherein the gas inlet (28) exits through said plate (20).

5 5. The apparatus according to claim 2 or 4, wherein the upper suction opening (32) has the shape of an annular gap.

6. The apparatus according to any of the preceding claims, wherein the vanes (22; 23) are arranged such that they extend from the periphery and a distance in-
10 wards towards the centre of the apparatus, and form an angle (α) with an imagined line running from the outermost point of attachment for respective vane and through the centre of the entire unit.

7. The apparatus according to any preceding claim, wherein the rotation
15 transferring means is a shaft (24) which is attached to the plate (20) in the centre of thereof.

8. The apparatus according to any of the preceding claims, wherein the shaft (24) is hollow and connected to a gas source via a throttle valve (30) for the supply
20 of gas to the inner of the apparatus via an opening (28) in the end of the shaft (24).

9. A method of treatment of contaminated media containing organic material, the method comprising the following steps:

25 providing a rotatable, cone shaped housing having an inlet and an outlet for medium to be treated;

immersing said housing in the medium to be treated;

30 rotating said housing such that a vortex is generated therein;

supplying gas to the center of said vortex.

10. The method according to claim 8, wherein the medium has a high concentration of bacteria, e.g. E. Coli.
35

WO 00/41802


PCT/SE00/00083

16

11. The method according to claim 8 or 9, wherein the medium is manure, waste water sludge, leak water from waste deposits.
- 5 12. The method according to any of claims 8-10, wherein the speed of rotation of the housing is 500-3500 rpm, preferably 800-2800 rpm.
13. The method according to any of claims 8-11, wherein the gas is air.
- 10 14. The method according to any of claims 8-11, wherein the gas is ozone.
15. The method according to any of claims 8-13, wherein an apparatus according to any of claims 1-6 is used.
- 15 16. A product obtained by treatment of a contaminated medium with the method according to any of claims 8-14.

4/5

Fig. 5



INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 00/00083

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B01F 3/04, B01F 7/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B01F, C02F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	CA 1101138 A (GUARNASCHELLI, CLAUDIO), 12 May 1981 (12.05.81), page 5, line 7 - page 6, line 30, figures 1-3 -----	1-8

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents

"A" document defining the general state of the art which is not considered to be of particular relevance

"B" earlier document but published on or after the international filing date

"I" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"F" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

11 May 2000

Date of mailing of the international search report

15-05-2000

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Wiva Asplund/ELY

Telephone No. +46 8 782 25 00

PATENT COOPERATION TREATY

PCT

NOTIFICATION OF ELECTION

(PCT Rule 61.2)

From the INTERNATIONAL BUREAU

To:

Assistant Commissioner for Patents
United States Patent and Trademark
Office
Box PCT
Washington, D.C. 20231
ETATS-UNIS D'AMERIQUE

in its capacity as elected Office

Date of mailing (day/month/year) 04 October 2000 (04.10.00)	
International application No. PCT/SE00/00083	Applicant's or agent's file reference PO4690PC/ALi
International filing date (day/month/year) 17 January 2000 (17.01.00)	Priority date (day/month/year) 15 January 1999 (15.01.99)
Applicant AHLSTRÖM, Rolf	

1. The designated Office is hereby notified of its election made:

☒ in the demand filed with the International Preliminary Examining Authority on:
28 July 2000 (28.07.00)

☐ in a notice effecting later election filed with the International Bureau on:

2. The election ☒ was
☐ was not

made before the expiration of 19 months from the priority date or, where Rule 32 applies, within the time limit under Rule 32.2(b).

The International Bureau of WIPO 34, chemin des Colombettes 1211 Geneva 20, Switzerland Facsimile No.: (41-22) 740.14.35	Authorized officer <p style="text-align: center; font-weight: bold;">Charlotte ENGER</p> Telephone No.: (41-22) 338.83.38
---	---

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ :

B01F 3/04, 7/00

A1

(11) International Publication Number:

WO 00/41802

(43) International Publication Date:

20 July 2000 (20.07.00)

(21) International Application Number: PCT/SE00/00083

(22) International Filing Date: 17 January 2000 (17.01.00)

(30) Priority Data:

9900104-2

15 January 1999 (15.01.99)

SE

(71) Applicant (for all designated States except US): GEFLE
VIRVELTEKNIK AB [SE/SE]; Båtmansgatan 15, S-802 84
Gävle (SE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): AHLSTRÖM, Rolf [SE/SE];
Luthergatan 6A, S-802 52 Gävle (SE).(74) Agent: LINDGREN, Anders; Dr. Ludwig Brann Patentbyrå
AB, Box 1344, S-751 43 Uppsala (SE).


(81) Designated States: AE, AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), DM, EE, EE (Utility model), ES, FI, FI (Utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published*With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*

(54) Title: DEVICE AND METHOD FOR THE TREATMENT OF CONTAMINATED MEDIA

(57) Abstract

The invention relates to an apparatus for the treatment of contaminated media, comprising a rotatable housing having at least one inlet (28) for gas emerging in the stirrer housing, and at least one suction opening (10; 32) for the medium to be treated. The housing is provided with a plurality of outlet openings (25; 27) arranged along its periphery. A plurality of vanes (22; 23) are arranged in the outlet openings (25; 27). A rotation transferring means (24) is provided to transfer a rotational movement to the stirrer. A method according to the invention comprises generating a vortex in the medium in such a way that an under-pressure occurs in the centre of the vortex, and that a nitrogen containing gas is introduced in the centre of the vortex.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Device and method for the treatment of contaminated media

The present invention relates to a device and a method for the treatment of strongly contaminated and nasty smelling media, and whenever applicable, treatment of media with very high contents of bacteria. The invention also relates to the products obtained when performing the method.

Background of the invention and prior art

In many fields nasty smelling and strongly contaminated media are produced. In the field of animal breeding manure is produced which releases large amounts of ammonia, which constitutes an environmental drawback for the near surroundings, but also for the environment as a whole. The bacteria contents can also be high, and direct contact with the manure can be extremely hazardous to the health.

Waste water arriving at sewage treatment plants in the form of a sludge having a high content of bacteria is also highly nasty smelling and must be taken care of in an environmentally friendly way. In larger sewage treatment plants sludge has traditionally been taken care of for the digestion thereof, in order to extract gas and killed bacteria, however, this is a laborious operation requiring large plants and much time. For smaller sewage treatment plants it is common to transport the sludge to plants having a treatment facility. It is also common to deposit the sludge at waste stations.

Regarding manure it is desirable to prevent ammonium from being released in the form of ammonia. This can be achieved by oxygenating the manure thereby producing a conversion of NH_4^+ -ions to NO_3^- -ions. One way of achieving this is to blow air through the medium by using compressors. However, this method is inefficient. The energy consumption is considerable and therefore the cost becomes high.

The sanitation aspect, i.e. the elimination of E. Coli from waste sludge and water has become increasingly important, and is to a great extent a problem.

A previously known device intended for the oxygenating of water having relatively low concentrations of solid compounds, i.e. not a sludge, is known from SE-460 706 and SE-500 416 respectively.

Canadian patent 1101138 discloses submerged turbine aeration apparatus. It comprises a hollow rotatable shaft, an intake for gas near the top end of the shaft, an outlet for gas near the bottom end of the shaft, and an impeller connected to the shaft. The impeller comprises two spaced-apart discs with a plurality of vane elements therebetween and an intake for liquid comprising an aperture adjacent the shaft for admitting the liquid. The impeller draws liquid through the aperture past the gas outlet, for mixing the liquid with the gas, and expels the liquid outwardly from the vane elements as the impeller rotates.

Although this device is usable for aeration of liquids, it cannot generate very high vortexes inside the impeller, because there is simply not enough space available.

Other examples of devices intended for oxygenating of liquids in various connections are known from e.g. US-5,275,762; US-5,045,202; US-4,442,045; WO 96/09989; WO 97/18168 and FR-2 277 044.

However, none of these devices anticipates the present invention.

Summary of the invention

Thus, there is a need to more efficiently take care of strongly contaminated and nasty smelling media that are formed e.g. in sewage treatment plants, e.g. raw sludge, and in animal breeding, e.g. pigs manure. Waste products from butcheries and garden waste materials such as composting waste material need to be taken care of in an efficient way.

The object of the invention is therefore to provide systems, devices and methods to achieve this.

This object is achieved in accordance with one aspect of the invention with the device according to claim 1. With this device, that can be said to constitute complex stirrer, a very efficient oxygenation of the contaminated medium is achieved, which contributes to nitrification processes occurring very rapidly. In addition a cavitation is created in the medium, which brings about a temperature increase, which also contributes to a very high killing of bacteria.

A substantial reduction in the BOD values have been noted, and oxygenation is very efficient in relation to the energy consumption when running the apparatus according to the invention.

5 It has also been noted that there are no losses of nitrogen, and certain indications point to the fact that the total nitrogen contents even increases in e.g. manure material, by treating media with the device and method according to the invention. Thus, the raw material is "refined" by performing the method according to the invention.

10

When performing the method according to the invention, which is defined in claim 9, a product is obtained in the form of a sludge which is virtually freed from bacteria, which has a certain concentration of nitrates and phosphorous, and which is particularly suitable as nutrition for forests and fields, plantations etc.

15

This sludge is very easy sedimentable such that supernatant with high concentrations of nitrate and a very compact sedimented rest is formed. This rest is excellent as earth improver and as a fertiliser. The supernatant can also be used for fertilising, e.g. for energy forests, nursery gardens, market gardens, city plantations etc.

20

The invention will now be further illustrated with reference to the attached drawings wherein

Fig. 1 shows the stirrer according to the invention in a perspective view;

25

Fig. 2 shows a view from above with the upper part of the stirrer taken away;

Fig. 3 shows a preferred embodiment of the stirrer according to the invention in cross section;

30

Fig. 4 shows another embodiment of the stirrer according to the invention having only one compartment;

35

Fig. 5 shows a still further embodiment of the stirrer according to the invention with only one compartment; and

Fig. 6 illustrates schematically the flow pattern in operation of the apparatus according to the invention.

Detailed description of the invention

5

The embodiment of a stirrer according to the invention shown in Fig. 1, and generally designated 2 in Fig. 1, comprises a stirrer housing. The housing in its turn comprises a first upper sheath 4 and a second lower sheath 6. The sheaths 4, 6 are essentially shaped as truncated cones, such that instead of a cone apex there are
10 openings 8, 10 facing upwards and downwards respectively. By making the upper and lower compartments of the stirrer as a double cone, the volume in each compartment will be large enough to enable the strong vortex, required for the effect according to the invention to take place.

15 The first (upper in the figure) sheath 4 has a flange or collar 12 running around its base 14. Correspondingly the second (lower in the figure) sheath 6 has a flange or collar 16 running around its base 18. Between both sheath units 4, 6 there is a circular plate 20 provided. The plate 20 is rigidly joined to respective sheath unit 4, 6 by way of upper vanes 22 provided on the upper side, and lower vanes 23 pro-
20 vided on the lower side of the plate 20. These vanes 22, 23 are arranged such that they extend from the periphery and a distance inwards towards the centre of the stirrer. However, they form an angle α together with an imagined line running from the point of attachment for respective vane and through the centre of the entire unit. This is most clearly evident from Fig. 2, which separately shows the circular
25 plate 20 comprising the upper vanes 22, seen from above. Between vanes 22, 23 there are formed upper outlet apertures 25 and lower outlet apertures. This part of the stirrer 10 will be referred to below as its "waist".

By this design the stirrer has two separate compartments, an upper compartment
30 5 and a lower compartment 7, the significance of which will be further illustrated with reference to the description of function below.

The length of the vanes 22, 23 is not critical, and can vary, but should preferably amount to between 20 and 70% of the diameter, calculated from the outer point of
35 attachment of the vanes along the periphery of the plate 20. Also the number of vanes is not critical but a suitable number of vanes should be 2-15, preferably 5-

10. The angle α is not particularly critical but should amount to 30-70°, and preferably it should be between 35 and 50°C.

A shaft is provided centrally and in axial direction. The shaft runs through the
5 plate 20, and its end surface 21 is situated in essentially the same plane as the
lower edge of the lower vanes 23, or expressed differently in the same plane as the
flange 16 belonging to the lower sheath 6. The shaft 24 has a central air channel
26 emerging in a hole 28 on the underside (as seen in the figures) of the plate 20.
See in particular Fig. 3. The shaft 24 is connected to a drive unit (not shown) to
10 provide rotation, e.g. an electric motor. The other upper end of the air channel is
closed. However, on the shaft there is provided a throttle valve 30. With this valve
30 the supply of air during operation can be varied, which will be described more
closely below. As shown in the figures, the shaft 24 can extend past the plate 20 to
a level equal to the lower edges of the vanes 23. This configuration is suitable for
15 the treatment of e.g. manure. Namely, because of the high viscosity thereof the
material would not be able to reach higher, e.g. up to the bottom side of the plate
20. However, for lower viscosity media, such as waste water, it is conceivable to
attach the shaft 24 directly onto the plate 20, and just make a hole in said plate
20, having a diameter corresponding to the diameter of bore or air channel 26 in
20 the shaft 24.

The shaft 24 protrudes through the upper opening 8 of the upper sheath unit 4,
such that an annular gap 32 is formed around the shaft 24. The annular gap 32
and the opening 10 serve as an inlet for flowing medium during operation of the
25 device, which will be further illustrated below.

The embodiment shown in Fig. 1-3 is a preferred variant, in that it performs dual
functions. The upper compartment and the air entering therein primarily contrib-
utes to oxygenation, while the lower compartments contributes to the killing of
30 bacteria and nitrification.

In a further embodiment of the design according to Fig. 3, the circular plate 20,
separating the upper and lower compartments 5 and 7 respectively, is provided
with a deflection collar 20b, forming an angle of about 30° (the angle is not strictly
35 critical) with the plane of said plate 20. This angled deflection collar serves to de-
flect the medium expelled from the lower compartment 7 downwards. This en-
hances the circulation of the medium inside the vessel significantly, and avoids gas

from escaping upwards and into the atmosphere. In fact, the strong vortex in the vessel and the downward movement of the expelled medium combine to make the expelled medium quickly reentering the lower compartment through the bottom inlet 10. In order to further enhance the effect of this flow improvement, preferably
5 a vessel is used where the lower portion is cone shaped.

In Fig. 4 there is shown a simpler variant wherein the upper compartment has been removed. In all other respects it is identical with the embodiment shown in Fig.3.

10 In the same way there is shown in Fig. 5, a variant wherein the lower compartment has been removed. For this purpose the shaft 24 is attached e.g. by means of welding in the plate 20, which forms a bottom. Radial holes 25 are bored through to the central air channel 26. In all other respects it is identical to the upper part of
15 the embodiment shown in Fig. 3. This variant can only be used for oxygenation.

Depending on the field of use the stirrer according to the invention can be differently dimensioned. It can be used in relatively small containers of a few hundred litres, up to very large containers of tens of cubic metres and even larger.

20 Another conceivable field of use is purification/oxygenation of water in lakes, whereby the stirrer could be made very large with a diameter of up to 1 m. Also water in fish breeding facilities could be treated in accordance with the invention.

25 Other conceivable fields of use are treatment of various types of manure such as manure from pigs and cows. Such manure types often contains straw and therefore need to be pre-treated by some kind of grinding process.

It is further conceivable to treat butchery wastes, leakage water from waste dumps,
30 process waters from industries, waste water from car wash facilities etc.

Still another use of the inventive idea is the removal of metals from waste waters, especially for the enhancement of the sedimentation rate of leachates from waste deposits. It is especially efficient for the improved separation of copper. For this
35 purpose a device according to Fig. 4 is used. It is believed that due to the extreme conditions created inside the stirrer housing, the Cu-microparticles will aggregate to larger assemblies that will sediment at a very much larger rate. It is also possible

that colloidal Cu is aggregated, which is a great improvement, since colloidal particles normally will not settle within a reasonable time, if at all, by currently used methods.

5 The device according to the invention is used in the following way.

A contaminated and possibly nasty smelling medium, e.g. pigs manure or sludge from waste water treatment plants, is placed in a suitably dimensioned tank. The stirrer is lowered down to the level in the tank. The driving motor is initiated and
10 the stirrer is caused to rotate. Depending on the desired effect, the speed of rotation is selected within different ranges.

- | | | |
|----|----|--|
| | 1: | For oxygenation only a speed of rotation is used in the range 800-2800 rpm |
| 15 | 2: | For treatment of manure 800-1500 rpm |
| | 3: | For treatment of sludge 800-1500 rpm |

When the stirrer begins to rotate the vanes 22 become operative, throwing material outwards from the centre of the stirrer. Thereby material is sucked in trough the
20 opening 10 at the lower end of the stirrer and through the annular gap 32 at its upper end. Since the device rotates, the material that has been sucked in is forced into a vortex type of movement which makes it strive outwards and flow along the inner surfaces of the sheaths 4, 6, and downwards and upwards respectively against the edges 14 and 18 of the sheaths, where it is thrown out from the stirrer
25 by centrifugal force. Because a strong vortex is formed in the medium around the stirrer the liquid level in the vortex will be lowered down to the upper opening of the stirrer. There, air will be sucked in vigorously. At a speed of rotation amounting to 1500 rpm a stirrer according to the invention having a diameter of 15 cm i.e. as it is shown in the figures, sucks in 15-20 m³/h into the medium. This can essentially
30 be varied by proportionally changing the dimension of the device. The oxygen in the air that has been sucked in trough the annular gap will oxygenate the medium and contribute to higher biological activity in the medium, i.e. microbiological decomposition (decay process) is strongly supported.

35 In the same or a corresponding way a strong vortex is formed in the medium above the lower opening 10, see Fig. 6 which schematically shows a set arrows indicating flow pattern vectors . That material will be drawn upwards because the vanes 23

through the material out from the lower compartment 7 and out through the peripheral openings 27 at the waist 29 of the stirrer. This creates a vacuum/under-pressure in the centre of the stirrer. The under-pressure is regulated by adjusting the throttle valve to a suitable extent, and by adapting the speed of rotation in accordance with the viscosity of the medium and its dry matter content. This is done empirically by testing. As can be seen in Fig. 6, the air that is introduced through the inlet 28 forms a very narrow "channel" 29 in the centre of the vortex. Thus, there will be a flow both outwards from the housing through the outlets 23, and an inward flow towards the centre. The gas in the narrow "channel", centrally located in the vortex, will diffuse into the medium and cause oxygenation thereof (if oxygen is present). In particular a point of implosion is formed as indicated at PI in the figure. Below the housing, a further vortex V_B is formed, which is clearly visible within boundaries indicated by the dashed lines. The visibility is due to the dispersion of very fine gas bubbles in the medium.

During operation the flow pattern will go through a cycling, the period of which can vary, but with the set up shown in the figures, amounts to about 30 seconds. The cycling can be defined by the movement of the central "air channel" which is formed at the opening 28 and gradually extends downwards, to subsequently reduce its extension and begin to "pull back" towards the opening 28 again.

Without wishing to be bound by any theory for the mechanism we believe that the following takes place in the stirrer.

Air or some other gas that is sucked in to the lower compartment in the stirrer housing through the air channel 26 in the shaft 24, will encounter extreme conditions due to the vacuum prevailing therein. The exact mechanism is not known, but it is believed that the extreme pressure conditions and the cavitation and possibly implosion that takes place in this region, can release nitrogen, if present in the gas, and possibly molecular nitrogen is formed, which can react with the organic material in the medium and form nitrogen compounds. The oxygen or ozone, if present, in the microscopic bubbles that are generated diffuse rapidly into the medium where organic material is oxidised. Aerobic bacteria in the medium will also consume oxygen. In the bubbles, nitrogen will remain which has properties different from those of oxygen. The extreme conditions contribute to the rapid conversion of NH_4^+ ions to NO_3^- ions. Also it is believed that the cavitation, will cause mechanical damage to the cells and thereby contribute to the killing of the bacteria.

The experiments that have been performed have verified very large killing rates of E. Coli.

- 5 The obtained product, e.g. treated sludge that has been allowed to sediment, is very suitable as earth-improver or manure, since the major part of the phosphorous that is present in the sludge is transferred to the dewatered portion.

10 The invention will now be closer illustrated with reference to examples, which are not to be regarded as limiting on the scope of the invention.

EXAMPLES

Example 1

15 Sludge from one of the sewage treatment plant of Gävle kommun was treated for 21 days with a stirrer according to the invention.

20 Approximately 0,3 m³ sludge was placed in a tank provided with a stirrer according to the invention. The process was run for 7 days without any addition of sludge. This period can be regarded as a "starting period". During this period the rotation of the stirrer was 1500 rpm. In order to simulate the flow in the sewage plant a 10% exchange of sludge everyday was initiated after 12 days.

25 In table 1 results of chemical and microbiological analysis are shown.

The time sequence of the experiment was the following:

30 The process was initiated on June 29 and continued until July 6 without any material being exchanged. July 6 the process was stopped and was halted during 5 days, and July 11 it was started again. Thereafter 10% of the sludge was exchanged every day. The processes was terminated July 29.

Table 1

Analysis	unit	June 29	July 6	July 11 restart	July 20
E. Coli	per 100 ml	22000000	34000	--	33000
Fecal streptococks	no analysis				
Dry matter (DM)	%	6.1	2.8	--	3.3
Burning loss	% of DM	63	60.3	--	60.4
Total nitrogen	% of DM	2.5	3.7	--	4.2
Ammonium nitrogen	% of DM	0.30	0.65	--	0.53
COD	mg/l	22900	21900	--	24700
BOD	mg/l	5600	850	--	2100

As can be seen from table 1 an (apparent) increase of the total nitrogen amounting to approximately 70% is noted. This increase can be due to an error in the analysis. Possibly depending on the nitrogen of the raw sludge being bound in a way that the analysis is not capable of identifying.

Further, the very large reduction of E. Coli can be noted. The residual content amounted to only about 0,15% of the initial content.

The treated sludge was essentially free from smell after 24 hours. One litre of the sludge was poured in a measuring cylinder, and was allowed to sediment for two days, i.e. until no further sedimentation could be seen. After this time it had sedimented to a very compact caking and a relatively clear supernatant.

In order to render the separation more efficient, sludge was filtrated whereby a caking and a supernatant was obtained. The caking was essentially free from smell (only phosphorous smell) and had the consistency of a compact clay.

The analysis of the supernatant yielded the following results:

Phosphate-P	0,3 mg/l
Total-P	0,9 mg/l
Nitrate-N	147 mg/l
Ammonium-N	8,5 mg/l
COD	280 mg/l

Analysis of dewatered sludge gave the following result:

Dry matter 9,63 %
 Burning loss 60,5 % of dry matter

5

Example 2

Sludge from the same sewage plant as in example 1 has been treated in a further run. The treatment was performed during 72 hours. The treated (stabilised) sludge was dewatered, and thereby one part dewatered sludge and one part almost colourless liquid was obtained. The sludge was essentially free from smell in less than 24 hours.

Table 2

15

ANALYSIS	unit	Nov. 30 (raw sludge)	Dec 3 (stabilised sludge)
E. COLI	per 100 ml	54 x 10 ⁹	700 000
AMMONIUM-N	% of DM	0,31	0,12
20 NITRITE	% of DM	0,004	0,08
NITRATE	% of DM	Not 1	0,47
TOTAL-N	% of DM	2,9	3,3
PHOSPHATE-P	Note 2	Note 2	

25 From stabilised sludge

	Dewatered sludge	Filtered liquid
E. COLI	per 100 ml	800 AMMONIUM-N
	% of DM	14 mg/l
NITRITE	% of DM	15 mg/l
30 NITRATE	% of DM	150 mg/l
TOTAL-N	% of DM	180 mg/l
PHOSPHATE-P	Note 2	0,15 mg/l

Note 1: The analysis could not be made due to the constitution of the sample

35 Note 2: Could not be analysed

Example 3

A further experiment with sample from the same sewage plant as in example 1 and 2 was performed. The following results were obtained:

Table 3

	Sludge	Dewatered sludge	Separated liquid
Dry matter	2,4%	7,3%	--
Total-P	2,3%	2,6%	1,4 mg/l
10 NO ₂ -N	17 mg/kg DM	42 mg/kg DM	0,68 mg/l
NO ₃ -N	670 mg/kg DM	52 mg/kg DM	38 mg/l
NH ₄ -N	280 mg/kg DM	900 mg/kg DM	21 mg/l
Total-N	3,0%	3,0%	47 mg/l

15 As is evident the nitrogen concentration has not been reduced.

Example 4

20 Leachate from a waste station (Forsbacka) was treated with the method and apparatus according to the invention. The following results were obtained.

Sample No.	Tr. time/h	Metal mg/l				
		Cu	Zn	Fe	Mn	Ni
25 0	0	0,67	0,68	34	3,4	0,064
1	1	0,03	0,70	24	3,2	0,033
2	24	0,03	0,26	18	0,73	0,035
Reduction (%):		96	62	47	79	35

30 As is evident from this table a significant reduction of metal contents is achieved.

Example 5

35 Pigs manure from a pig stable was placed in a tank of 0,3 m³, and was exposed to the same treatment as the sludge in example 1. This manure contained large por-

tions of urine and straw. The very strong smell (ammonia) was reduced after 36 hours to stable and straw smell. After the process had been started the temperature exceeded the ambient temperature by 25-30°C.

5 Example 6

The product obtained after treatment of sludge is sedimented and the sediment is separated. After drying it is used as earth improver for the growing of tomatoes. In comparison with tomatoes that have not obtained earth improver, one can observe
10 a marked difference in growth power.

Example 7

Supernatant from the sedimentation experiment in Example 1 contains nitrogen
15 bound in the form of NO_3 which renders it usable as manure water for the growth of potatoes, tomatoes, flax etc.

An important observation is that the temperature of the medium during treatment according to the invention is of importance for the final product. It has turned out
20 that the temperature should be between 10 and 25°C. It can be noted that the optimal temperature for oxygenating water is 22°C.

Therefore, it is preferred that the medium to be treated be taken directly from the process in which it is generated, such as paper pulp production, chemical process
25 liquids etc.

CLAIMS:

1. An apparatus for the treatment of contaminated media, comprising a rotatable housing having at least one inlet (28) for gas and at least one suction opening (10; 32) for the medium to be treated; a number of outlet openings (25; 27) arranged along the periphery of the housing; a number of vanes (22; 23) arranged in said outlet openings (35; 27); and a shaft (24) connected to the housing and connectable to a device for causing rotation of the housing;

10 c h a r a c t e r i z e d i n t h a t

the housing comprises at least one compartment which is essentially shaped as a truncated cone, with the inlet (10; 32) for the medium to be treated at the apex of the cone and the outlets (25; 27) at the base thereof.

15

2. The apparatus according to claim 1, wherein

said housing comprises an upper compartment (5) with a corresponding upper suction opening (32) and a lower compartment (7) with a corresponding lower suction opening (10), where the upper and the lower compartments are separated by a plate (20); and wherein

20

the plurality of outlet opening (25; 27) provided along the periphery of the housing or housings belong to the upper (5) and the lower (7) compartments respectively, at the opposite end thereof with respect to the corresponding suction opening (32, 10).

25

3. The apparatus according to claim 1, wherein said housing comprises one single compartment (7) having the shape of a truncated cone with the apex facing downwards, and having a suction opening (10) at the apex of said cone, and a plate (20) forming the base of said cone and closing said compartment (7), and wherein the gas inlet (28) exits through said plate (20).

30

4. The apparatus according to claim 1, wherein said housing comprises one single compartment (7) having the shape of a truncated cone with the apex facing

35

upwards, and having a suction opening (32) at the apex of said cone, and a plate (20) forming the base of said cone and closing said compartment (7), and wherein the gas inlet (28) exits through said plate (20).

- 5 5. The apparatus according to claim 2 or 4, wherein the upper suction opening (32) has the shape of an annular gap.
6. The apparatus according to any of the preceding claims, wherein the vanes (22; 23) are arranged such that they extend from the periphery and a distance in-
10 wards towards the centre of the apparatus, and form an angle (α) with an imagined line running from the outermost point of attachment for respective vane and through the centre of the entire unit.
7. The apparatus according to any preceding claim, wherein the rotation
15 transferring means is a shaft (24) which is attached to the plate (20) in the centre of thereof.
8. The apparatus according to any of the preceding claims, wherein the shaft (24) is hollow and connected to a gas source via a throttle valve (30) for the supply
20 of gas to the inner of the apparatus via an opening (28) in the end of the shaft (24).
9. A method of treatment of contaminated media containing organic material, the method comprising the following steps:

25 providing a rotatable, cone shaped housing having an inlet and an outlet for medium to be treated;

immersed said housing in the medium to be treated;

30 rotating said housing such that a vortex is generated therein;

supplying gas to the center of said vortex.
10. The method according to claim 8, wherein the medium has a high concentration of bacteria, e.g. E. Coli.
35

11. The method according to claim 8 or 9, wherein the medium is manure, waste water sludge, leak water from waste deposits.
- 5 12. The method according to any of claims 8-10, wherein the speed of rotation of the housing is 500-3500 rpm, preferably 800-2800 rpm.
13. The method according to any of claims 8-11, wherein the gas is air.
- 10 14. The method according to any of claims 8-11, wherein the gas is ozone.
15. The method according to any of claims 8-13, wherein an apparatus according to any of claims 1-6 is used.
- 15 16. A product obtained by treatment of a contaminated medium with the method according to any of claims 8-14.

1/5

Fig. 1






Fig. 2



2/5

Fig. 3



3/5

Fig. 4





Fig. 5



5/5

Fig. 6

